

Date

Name

Client

Project Name



Quote#

Type/Quantity

OBLIX 40

220 74 12

[Web-Link](#)



Erhältliche Farben: ALU GRAU (220 74 12 A)
DUNKELGRAU (220 74 12 N)

INCL. 1 x POWERLED WHITE 6,2W / CRI>80 / 3000K / 703lm
INCL. LED POWER SUPPLY 350mA-DC

LED Technik: Lichtquelle: 703 lm // 6.2 W // 113 lm/W
Leuchte: 511 lm // 7 W // 72 lm/W

100-240V / 50-60Hz

Klasse: II

Gewicht: 2.2 KG

Schutzpegel: IP55

Mindestabstand: nicht zutreffend

Optionen: PLATE 7
PIN 12
CBOX
IP68 CONNECTION KIT
IP68 CONNECTOR 3P

Detaillierte Installationsanweisungen finden Sie in der Bedienungsanleitung nach: [220 74 12 HAND.pdf](#)


OBLIX 40

220 74 12

Zugehörige Referenzen


WASSERDICHTHE VERBINDUNGSTEILE

[Web-Link / Datenblatt](#)




CBOX
216 12 00

[Web-Link / Datenblatt](#)



IP68 CONNECTION KIT
216 12 01

[Web-Link / Datenblatt](#)




IP68 CONNECTOR 3P
216 12 02

Zugehörige Referenzen

ERDSPIEßE UND PLATTEN FÜR POLLER

[Web-Link / Datenblatt](#)



PIN 12
229 01 12

[Web-Link / Datenblatt](#)



PLATE 7
229 02 07

OBLIX 40
220 74 12

Projektbild

